

PRODUCT DATA SHEET

Direct thermal synthetic 75 HM CCK70

Issued Date : 02.01.2019

Facestock

Direct thermal synthetic

9400

It is BOPP based, one side direct thermal printable layer coated and other side corona treated film with high definition imaging on bright white , heat sensitive surface , moisture and abrasion resistance and a general purpose for logistics , food , luggage tag...

Typical values

Grammage	ISO 536	gsm	60
Caliper	ISO 534	µm	75

Adhesive

Homelt

P

Pressure sensitive hot melt adhesive for labels, with high tack and peel properties, good wetting to substrates and oil resistance , as well as good die-cuttability

Typical values

Loop Tack	FTM 9	High
Final adhesion	FTM 1	High
Application temperature		0°C - 40°C
Service temperature range		- 20°C/+50°C

Liner

CCK70

Siliconised white clay coated kraft liner with excellent lay flatness .

Typical values

Grammage	ISO 536	gsm	70 ± 7
Caliper	ISO 534	µm	69 ± 4

Shelf life

1 year when stored at 22 °C and 50% rH

PANOVAL disclaims all conditions and warranties, whether express or implied, including the implied warranties of fitness for a particular purpose or merchantability. PANOVAL shall not be responsible for consequential, indirect or incidental damages (including loss of profits) of any kind. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product described herein should be verified by testing and carried out only by qualified experts . It is the sole responsibility of the customer to carry out and arrange for any such testing.

All information is subject to change without notice

PANOVAL Asia , Lot E9 – 2B , Street 1 , Hiep Phuoc Industrial Park, Nha Be Province , Ho Chi Minh City Vietnam info@panoval.com www.panoval.com