



PRODUCT DATA SHEET

PP50C TC UVHOTMELT PET30C

Issued Date : 20.01.2019

Facestock

PP50C TC

9200

High transparent polypropylene film (BOPP) with a glossy finish. The top coating allows excellent ink adhesion and good performance with UV printing technologies .

Typical values

Grammage	ISO 536	gsm	45
Caliper	ISO 534	µm	50

Adhesive

UVHOTMELT

UVHM

A UV-curable hotmelt pressure sensitive adhesive with high tack and peel values

Food contact

Compliance with FDA 21 CFR 175.105

Typical values

Loop Tack	FTM 9	High
Final adhesion	FTM 1	High
Application temperature		0°C - 40°C
Service temperature range		- 20°C/+50°C

Liner

PET30C

Siliconised Polyester film with outstanding clarity and smoothness. It is idea for ‘ no-label-look ‘ self-adhesive labels .

Typical values

Grammage	ISO 536	gsm	41
Caliper	ISO 534	µm	30

Shelf life

1 year when stored at 22 °C and 50% rH

PANOVAL disclaims all conditions and warranties, whether express or implied, including the implied warranties of fitness for a particular purpose or merchantability. PANOVAL shall not be responsible for consequential, indirect or incidental damages (including loss of profits) of any kind. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product described herein should be verified by testing and carried out only by qualified experts . It is the sole responsibility of the customer to carry out and arrange for any such testing.

All information is subject to change without notice

PANOVAL Asia , Lot E9 – 2B , Street 1 , Hiep Phuoc Industrial Park, Nha Be Province , Ho Chi Minh City Vietnam info@panoval.com www.panoval.com